

Xprinter®

Impact Dot matrix Printer


XP-D76EC

- Support Chinese GB18030
- Transfer simplified/traditional Chinese by using commands
- Avoid order missing
- Black mark orientation
- Imported Citizen DP332 printing head



XP-D76EC

Impact Dot matrix Printer



Printing		XP-D76EC
Printing method	9-Pin serial impact dot-matrix printing	
Printing width	63.5mm	
Print Resolution	72 dpi (Horizontal)/ 144 dpi (Vertical)	
Printing speed	4.5 line/s	
Interface	Serial+USB+Lan	
Printing paper	75.5±0.5mm×φ80mm(max)	
Character size	ANK, Font A: 1.6×3.1mm (9×9 dots) Font B: 1.2×3.1mm (7×9 dots) Chinese, traditional Chinese: 2.7×2.7mm (16×16 dots)	
Column number	Font A - 33 columns / Font B - 40 columns / Chinese, traditional Chinese - 22 columns	
Character		
Extension character sheet	PC437/Katakana/PC850/PC860/PC863/PC865/WPC1252/PC866/PC852/PC858	
Power		
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Cutter		
Auto cutter	Partial	
Software		
Driver	Windows / Linux / Mac	
Utility	Windows	
SDK	Windows / Android	
Physical characteristics		
Weight	2.2 KG	
Dimensions	247×156×143mm (D×W×H)	
Environmental Requirements		
Work environment	0 ~ 45℃, 10 ~ 80% RH	
Storage environment	-10 ~ 60℃, 10 ~ 90% RH (no condensation)	
Reliability		
Cutter lif	1 million cuts	
Printer head life	10 Million Lines	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

