

XP-MP03

Panel Printer



Key features

- Mini size, light and multi-functions
- Easy to operate and connect
- Fast speed, high quality and stylish appearance

Applications



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

XP-MP03

Panel Printer



Printing		XP-MP03
Printing method	Direct thermal	
Paper width	58 mm or 60mm	
Print width	48 mm	
Column capacity	384 dots/line	
Printing speed	90 mm/s	
Interface	Serial+Parallel	
Line spacing	3.75mm	
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, traditional Chinese:3.0×3.0mm (24×24 dots)	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Power		
Power source input	DC 12V/2.6A	
Cash drawer output	DC: 12V/1A	
Physical characteristics		
Weight	0.16 KG	
Dimensions	140*142*110.7mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature: 0~45℃ humidity : RH 10 ~ 80%	
Storage environment	Temperature: -10~60℃ humidity: RH 10~90℃	
Reliability		
Printer head life	50 KM	



Scan QR code to checkout Xprinter website for more update information.
 Phone: (+86 756) 3895 852
 Http://www.xprintertech.com
 Email: overseas@xprinter.net

